



FPS Series

0.1 – 15GHz Divide-By-5 Prescaler

Features

- Input Frequency: 0.1-15GHz
- Output Frequency:0.02-3GHz
- Divide Ratio: 5
- Output Power: 3dBm
- Phase Noise: -153dBc/Hz
- DC Power: 5V/205mA
- SMA Connector

Description

FPS-5-15 is a wideband frequency 0.1 – 15GHz divider with divide ratio of 5.

Electrical Specifications @ +25 °C, Z_S = Z_L = 50 Ohms


Parameter	Unit	Minimum	Typical	Maximum
Input Frequency Range	GHz	0.1		15
Output Frequency Range	GHz	0.02		3
Fixed Divide Ratio		5		
Input Power Range				
f = 0.1GHz – 0.25GHz	dBm	4		+10
f = 0.25GHz – 1GHz	dBm	-4		+10
f = 1GHz – 2GHz	dBm	-18		+10
f = 2GHz – 10GHz	dBm	-24		+10
f = 10GHz – 15GHz	dBm	-19		+10
Output Power				
f = 0.1GHz – 1GHz	dBm		+5	
f = 1GHz – 10GHz	dBm	+3	+4	
f = 10GHz – 15GHz	dBm	+2	+3	
SSB Phase Noise (100KHz Offset)	dBc/Hz		-153	
DC Power Supply	V		5	
Supply Current	mA		205	



Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Input Power	+13dBm
Supply Voltage	+16V
Operating Temperature	-40 °C to +85 °C
Storage Temperature	-55 °C to +125 °C

Outline



	A	B	C	D	E	F	G	H	I	J
Inch	1.250	1.250	0.563	0.450	1.000	0.625	1.000	0.250	0.500	0.187
mm	31.75	31.75	14.29	11.43	25.40	15.88	25.40	6.35	12.70	4.76