

## 900 MHz, 25Watt Amplifier **Outdoor unit**

This high power, bi-directional amplifier is designed for 902~928 MHz radio products. Works equally well with all types of radios.

Designed in a completely weatherproof housing for all outdoor applications. The unit is powered over coax with DC injector.



Item # 90325

## **Salient Features:**

- Transmit Gain: The unit provides 20 dB of gain which can be reduced at factory.
- LNA: The built-in Low Noise Amplifier with signal gain of 19 dB with a ultra low noise figure of only 2. 1.2dB. Improves the receive sensitivity of remote equipment, while keeping noise level very low.
- 3. Receive Filtering: All radio equipment contain filter for receive path. The band pass filter on this amplifier gives added protection against out of band noise.
- 4. Enclosure: The unit is housed in machined, Anodized Aluminum enclosure, designed according to the location of critical components. With appropriate cavities and contacts the PCB performs optimally and NO heat sink is needed.
- DC Injector: With only 0.8dB insertion loss, this DC injector is the lowest loss available anywhere. 5. Enclosed in a specially designed machined aluminum housing.
- 6. **Warranty**: All Shireen's products come with 2-year warranty.

## The complete set includes:

- The Outdoor Amplifier, 1.
- DC injector, and 2.
- Universal power supply (110~240VAC to 28 V DC)

## **Specifications**

Electrical:

Operating Range 902 - 928 MHz

Operating Mode TDD, Time Division duplex,

Transmit Power 44 dBm, 25 Watt Transmit Gain 20 dB max

Transmit input Power 0 dBm min 24 dBm max

Receive Gain 26 dB Noise Figure 1.2 dB

LED indicators Red for Receive (Default mode)

Green for Transmit

**Power Consumption** 260mA Rx, 1300 mA Tx @ 28VDC

Operating Temp -40 °C to + 70 °C

Mechanical:

**DC** Injector Amplifier

Dimension: 6" x 3.5" x 1.2" 1.4" x 3.5" x 1.0"

(152.4mm x 88.9mm x 41.91mm) (35.5mm x 88.9mm x 25.4)

Watertight machined aluminum housing with Enclosure: Machined aluminum housing with Anodized finish

Anodized finish

Connectors: Type N female Type N female

Weight: 1.51 lb (685 g) 2 Oz. (134 g)